# **TECHNICAL DATA SHEET**

# **BIOCLEAR LIQUID**

#### WHAT IS IT?

- Broad-spectrum rapidly acting organic waste degrader
- Anaerobic and aerobic process enhancer
- Multi-spore bacterial blend combined with surfactants and builders to promote activity and product stability

#### WHY WOULD I USE IT?

If you want to:

- Reduce the accumulation of grease mats in your collection systems
- Specifically target and eliminate fats, oils, and greases
- Eliminate odour-causing H2S, mercaptans, amines, and ammonia
- Prolong float and pump lifespan in your collection system
- Minimize system maintenance and downtime

# WHEN CAN I USE IT? (OPTIMUM CONDITIONS)

#### **BioClear Liquid performs best:**

- Within a range of pH 6.0 9.0 • Optimum activity near pH 7
- Within a temperature range of 5 °C to 40 °C
  - Optimum activity as temperatures near 37 °C

# **SPECIFICATIONS**

Description Packaging	White , citrus scented, free- flowing liquid 20kg pail
Bacteria	Proprietary blend of Bacillus spores
Nutrient	Biological nutrients, surfactants, and stimulants
	Sumulants

#### WHERE WOULD I USE IT?

- Lift Stations
- Grease Traps
- Treatment Plants
- Activated Sludge Systems

# HOW DO I USE IT?

Inject 4L per 1,000,000L (1 gal per 250,000 gpd) of flow where FOG mats are building up in lift stations, pump wells, and wet wells. This will help achieve optimum bacterial activity in your system. After 1 month of following recommended dosage you will start seeing noticeable positive benefits.

#### **STORAGE**

#### Shelf Life

Use within 6 months after opening.



Store in a cool dry place with good ventilation

Avoid direct Wash hands thoroughly sunlight after using

For Safety Data Sheet (SDS) and to learn more about our BioClear line of products call 1-800-387-7503 or visit us at www.cleartech.ca.



#### www.cleartech.ca

