

Section 01 Identification

Product Identifier Hydrochloric Acid 10-35% Solution

Hydrochloric Acid 10% NSF® - 60
Hydrochloric Acid 12% NSF® - 60
Hydrochloric Acid 15% NSF® - 60
Hydrochloric Acid 17% NSF® - 60
Hydrochloric Acid 20% NSF® - 60
Hydrochloric Acid 21% NSF® - 60
Hydrochloric Acid 27% NSF® - 60
Hydrochloric Acid 28% NSF® - 60
Hydrochloric Acid 29% NSF® - 60
Hydrochloric Acid 31% NSF® - 60
Hydrochloric Acid 31.45% NSF® - 60
Hydrochloric Acid 35% NSF® - 60

Other Means of Identification

Product Use and Restrictions

on Use

Aqueous hydrogen chloride, muriatic acid, hydrogen chloride, HCI, chlorohydric acid.

Acidizing (activation) of petroleum wells, scale removal, ore reduction, metal cleaning, pH adjustment, industrial acidizing, generation of chlorine dioxide, regeneration of ion

exchange resins. This product is NSF certified for use in drinking water, see section 15 and

the NSF website for further information.

Initial Supplier Identifier ClearTech Industries Inc.

1500 Quebec Avenue Saskatoon, SK. Canada

S7K 1V7

Phone: 800.387.7503 Fax: 888.281.8109 www.cleartech.ca

Prepared By ClearTech Industries Inc. technical writer

24-Hour Emergency Phone 306.664.2522

Section 02 Hazard Identification

Physical Hazards

Corrosive to metals Category 1

Health Hazards

Acute toxicity - inhalation Category 4
Acute toxicity - oral Category 4
Skin corrosion / irritation Category 1B
Serious eye damage / eye Category 1
irritation

Specific target organ toxicity - Category 3

single exposure

Signal Word

Customer Service: 800.387.7503 www.cleartech.ca Emergency: 306.664.2522

Revision Date: August 22, 2023

Emergency: 000:00 1:2022

Page 1 of 9

Danger

Hazard Statements

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

Pictograms



Precautionary Statements

Prevention

P234 Keep only in original packaging.

P260 Do not breathe vapours, fumes, or mists.

P264 Wash affected body parts thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves, protective clothing, eye protection, face protection.

Response

P301 P312 P330 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor if

P331 you feel unwell.

P303 P361 P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or

P363 shower. Wash contaminated clothing before reuse.

P304 P340 P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a

POISON CENTER or doctor.

P305 P351 P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P390 Absorb spillage to prevent material damage.

Storage

P403 Store in a well-ventilated place.

P233 Keep container tightly closed.

P405 Store locked up.

Disposal

P501 Dispose of contents / container in accordance with all federal, provincial and / or local regulations including the Canadian Environmental Protection Act.

Hazards Not Otherwise Classified

Not available

Supplemental Information

Customer Service: 800.387.7503 www.cleartech.ca Emergency: 306.664.2522 Revision Date: August 22, 2023

Page 2 of 9

Not available

Section 03 Composition / Information on Ingredients

Hazardous Ingredients:

Chemical name Common name(s) CAS number Concentration (w/w%)

Hydrogen Chloride Hydrochloric Acid 7647-01-0 10-36%

Section 04 First-Aid Measures

Description of necessary first-aid measures

Inhalation Take precautions to ensure your own safety before attempting a rescue (wear appropriate protective

equipment, use the buddy system). Remove source of exposure or move person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor. If breathing has stopped, trained personnel should begin rescue breathing or if the heart has stopped, immediately start cardiopulmonary resuscitation (CPR) or automated external defibrillation (AED). Avoid mouth to mouth contact by using a barrier device. Call a POISON CENTER or doctor if you feel unwell.

Ingestion Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor. If vomiting occurs

naturally, lie on your side, in the recovery position.

Skin Avoid direct contact. Wear chemical protective clothing, if necessary. Take off immediately contaminated contact clothing, shoes and leather goods. Rinse skin with lukewarm, gently flowing water / shower for 30 minutes.

Immediately call a POISON CENTER or doctor. Wash contaminated clothing before re-use, or discard.

Eye Avoid direct contact. Wear chemical protective gloves, if necessary. Remove source of exposure or move contact person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while

> holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for 30 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. Immediately call a

POISON CENTER or doctor.

Most important symptoms and effects, both acute and delayed

Inhalation Causes severe burns to the mouth and throat (mist). Harmful if inhaled. May cause respiratory

irritation.

Causes burns to the mouth and throat. Harmful if swallowed. Ingestion

Skin contact Causes severe skin burns. Eye contact Causes serious eye damage.

Further information For further information see Section 11 Toxicological Information.

Section 05 Fire Fighting Measures

Suitable extinguishing media Extinguish fire using extinguishing agents suitable for the surrounding fire.

Unsuitable extinguishing media

Water jets are not recommended in fires involving chemicals.

Specific hazards arising from

the chemical

Reacts with many metals to liberate hydrogen gas that can form explosive mixtures. Heat may liberate corrosive and toxic Hydrogen Chloride gas. Hydrogen Chloride is denser than

air and will accumulate in low lying areas.

Special protective equipment

for fire-fighters

Wear NIOSH-approved self-contained breathing apparatus and chemical-protective

clothing.

Customer Service: 800.387.7503 www.cleartech.ca Emergency: 306.664.2522 Revision Date: August 22, 2023

Section 06 Accidental Release Measures

Personal Precautions / **Protective Equipment / Emergency Procedures** Wear appropriate personal protective equipment (See Section 08 Exposure Controls and Personal Protection). Stay upwind, ventilate area. Do not breathe vapours, fumes, or mists.

Do not use material handling equipment with exposed metal surfaces.

Environmental Precautions Prevent material from entering waterways, sewers or confined spaces. Notify local health

and wildlife officials. Notify operators of nearby water intakes.

Methods and Materials for Containment and Cleaning

Up

SMALL SPILLS: Stop or reduce leak if safe to do so. Clean up spill with non-reactive absorbent and place in suitable, covered, labeled containers. Flush area with water. Contaminated absorbent material may pose the same hazards as the spilled product. LARGE SPILLS: Contact fire and emergency services and supplier for advice.

Section 07 Handling and Storage

Precautions for Safe Handling Use proper equipment for lifting and transporting all containers. Use sensible industrial hygiene and housekeeping practices. Wash thoroughly after handling. Avoid all situations that could lead to harmful exposure. Prevent the release of vapours, fumes, or mists into the workplace air.

> Inspect containers for damage or leaks before handling. If the original label is damaged or missing replace with a workplace label. Have suitable emergency equipment for fires, spills

and leaks readily available.

Never add water to a corrosive. Always add corrosives to water. When mixing with water, stir small amounts in slowly. Use cold water to prevent excessive heat generation. Never

return contaminated material to its original container.

Conditions for Safe Storage Store in a cool, dry, well-ventilated area, away from heat sources and incompatible

materials. Always store in original labeled container. Keep containers tightly closed when not in use and when empty. Empty containers may contain hazardous residues. Protect

label and keep it visible. Do not transfer to metal containers.

Incompatibilities Bases, such as potassium hydroxide, sodium hydroxide, calcium hydroxide (slaked lime),

ammonia, carbonates.

Metals, such as aluminum, steel, and brass.

Section 08 Exposure Controls and Personal Protection

Exposure limits

Component Regulation Type of listing Value Hydrogen Chloride **ACGIH TLV-Ceiling** 2 ppm

Engineering controls

Ventilation Requirements Mechanical ventilation (dilution or local exhaust), process or personnel enclosure and

control of process conditions should be provided in accordance with all fire codes and regulatory requirements. Supply sufficient replacement air to make up for air removed by

exhaust systems.

Other An emergency shower and eyewash station should be available, tested, and be in close

proximity to the product being handled in accordance with provincial regulations.

Protective equipment

The following are recommendations only. It is the responsibility of the employer / user to conduct a hazard assessment of the process in which this product being used and determine the proper engineering controls and PPE for their process. Additional regulatory and safety information should be sought from local authorities and, if needed, a professional industrial hygienist.

Customer Service: 800.387.7503 www.cleartech.ca Emergency: 306.664.2522 Revision Date: August 22, 2023

Eye and face protection

Where there is potential eye or face exposure, tightly fitting safety goggles and a face shield or a full face respirator or similar protective equipment which protects the wearer's face and eyes are recommended. Contact lenses are not recommended; they may contribute to severe eye injury.

Hand and body protection

Disposable latex or nitrile gloves are recommended to prevent incidental contact. Butyl rubber, neoprene, or PVC skin protection is recommended for extended contact. Leather gloves are not recommended for chemical protection. Refer to manufacturer's specifications for breakthrough times and permeability information; note that breakthrough times and permeability vary with temperature, application and age of material. Continued use of contaminated safety gear or clothing is not recommended; wash before reuse or discard.

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment.

NIOSH respirator recommendations for: Hydrogen Chloride

Up to: 50 ppm

(APF = 10) Any chemical cartridge respirator with cartridge(s) providing protection against Hydrogen Chloride

(APF = 10) Any supplied-air respirator

(APF = 25) Any powered, air-purifying respirator with cartridge(s) providing protection against Hydrogen Chloride

(APF = 50) Any air-purifying, full-facepiece respirator (gas mask) with a chin-style, front- or back-mounted canister providing protection against Hydrogen Chloride

(APF = 50) Any self-contained breathing apparatus with a full facepiece.

Emergency or planned entry into unknown concentrations or IDLH conditions:

(APF = 10,000) Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode

(APF = 10,000) Any supplied-air respirator that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary selfcontained positive-pressure breathing apparatus

Escape:

(APF = 50) Any air-purifying, full-facepiece respirator (gas mask) with a chin-style, front- or back-mounted canister providing protection against Hydrogen Chloride Any appropriate escape-type, self-contained breathing apparatus

Thermal hazards

Not available

Section 09 Physical and Chemical Properties

Appearance

Physical state Liquid

Colour Colourless to straw coloured

Odour **Pungent** Odour threshold 1-5 ppm

Property

pН <1.0

Melting point / freezing point For product concentration range: -57 to -27 °C Initial boiling point and For product concentration range: 62-90 °C

boiling range

Customer Service: 800.387.7503 www.cleartech.ca Emergency: 306.664.2522 Revision Date: August 22, 2023

Flash point

Evaporation rate

Flammability

Upper flammable limit

Lower flammable limit

Not applicable

Not applicable

Not applicable

Vapour pressure For product concentration range: negligible to 200 mmHg @ 20 °C

Vapour density 1.268

Relative density

Solubility

Not applicable

Soluble in water

Partition coefficient: n
Not available

octanol/water

Auto-ignition temperatureNot applicableDecomposition temperatureNot availableViscosityNot available

Specific gravity For product concentration range: 1.046-1.188 g/mL @ 20 °C

Particle characteristics Not applicable

Formula HCI

Molecular weight 34.46 g/mol

Section 10 Stability and Reactivity

Reactivity May be corrosive to metals. Reacts with many metals to liberate hydrogen gas that can

form explosive mixtures. Reacts with water to generate heat. Reacts violently with bases.

Stability This product is stable if stored according to the recommendations in Section 07.

Possibility of hazardous

reactions

Hazardous polymerization is not known to occur.

Conditions to avoid Avoid contact with incompatible materials.

Incompatible materialsBases, such as potassium hydroxide, sodium hydroxide, calcium hydroxide (slaked lime),

ammonia, carbonates.

Metals, such as aluminum, steel, and brass.

Hazardous decomposition

products

Not available

Section 11 Toxicological Information

Acute Toxicity (LD50 / LC50 values)

Component	Route	Species	Value	Exposure time
Hydrogen Chloride	Oral	Rat	238-277 mg/kg	
	Dermal	Mouse	1449 mg/kg	
	Inhalation (gas)	Mouse	1108 ppm	1 hour
	Inhalation (mist)	Guinea pig	2.0 mg/L	30 minutes

Toxic Health Effect Summary

Chemical Hydrogen chloride rapidly dissociates and most of it's toxic effects are thought to be the result of pH

characteristics change.

Revision Date: August 22, 2023

Customer Service: 800.387.7503 www.cleartech.ca Emergency: 306.664.2522

Page 6 of 9

Skin Causes severe skin burns.

Ingestion Causes burns to the mouth and throat. Harmful if swallowed.

Inhalation Causes severe burns to the mouth and throat (mist). Harmful if inhaled. May cause respiratory

irritation. Hydrogen chloride gas is severely irritating to all mucous membranes.

Eye contact Causes serious eye damage.

Sensitization This product and its components at their listed concentration have no known sensitizing effects.

Mutagenicity This product and its components at their listed concentration have no known mutagenic effects.

Carcinogenicity IARC has classified this product or one or more of its components as group 3, not classifiable as to its

carcinogenicity to humans.

Reproductive toxicity

This product and its components at their listed concentration have no known reproductive effects.

Specific organ

toxicity

Frequent contact may lead to dermatitus. Dental decay, with changes in tooth structure, yellowing, softening and breaking of teeth, and related digestive diseases are frequent after exposures to

hydrochloric acid

Aspiration hazard

d Not available
Not available

Synergistic materials

Section 12 Ecological Information

Ecotoxicity

Component	Type	Species	Value	Exposure Time
Hydrogen Chloride	LC50	Freshwater fish	20.5 mg/L	96 hours
	EC50	Freshwater invertabrates	0.45 mg/L	48 hours
	EC50	Freshwater algae	0.73 mg/L	72 hours

Biodegradability The domestic substance list categorizes hydrochloric acid as persistent.

Bioaccumulation The domestic substance list categorizes hydrochloric acid as non-bioaccumulative.

Mobility This product is water soluble, is not predicted to adsorb to soil and may contaminate ground

water. This product will evaporate and may be spread via wind.

Other adverse effects Not available

Section 13 Disposal Considerations

Waste From Residues /

Unused Products

Dispose in accordance with all federal, provincial, and local regulations including the

Canadian Environmental Protection Act.

Contaminated Packaging Do not remove label, follow label warnings even after the container is empty. Empty

containers should be recycled or disposed of at an approved waste handling facility.

Section 14 Transport Information

UN number UN1789

UN proper shipping name

and description

HYDROCHLORIC ACID

Transport hazard class(es) 8
Packing group ||

Revision Date: August 22, 2023

Customer Service: 800.387.7503 <u>www.cleartech.ca</u> Emergency: 306.664.2522

Page 7 of 9

Excepted quantities

Environmental hazards

Special precautions

Transport in bulk

1 L

Not listed as a marine pollutant under Canadian TDG Regulations, schedule III.

No special precautions ERAP index: 3000 L

MARPOL 73/78 and IBC Code:

Product name: Hydrochloric Acid

Pollution category: Z

the product is included in the Code because of both its safety Hazards:

and pollution hazards.

Ship type: ship type 3

Tank type: independent gravity tank

Tank vents: controlled venting

Tank environmental control: no special requirements under this Code

Temperature classes

Electrical equipment: Apparatus group

Flash point non-flammable product

Gauging: restricted gauging Vapour detection: toxic vapours

Fire protection: no special requirements under this Code

Emergency equipment see 14.3.1

Specific and operational 15.11

requirements

Additional information

Secure containers (full or empty) during shipment and ensure all caps, valves, or closures are secured in the closed position.

TDG PRODUCT CLASSIFICATION: This product has been classified on the preparation date specified at section 16 of this SDS, for transportation in accordance with the requirements of part 2 of the Transportation of Dangerous Goods Regulations. If applicable, testing and published test data regarding the classification of this product are listed in the references at section 16 of this SDS.

Section 15 Regulatory Information.

NOTE: THE PRODUCT LISTED ON THIS SAFETY DATA SHEET HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CANADIAN HAZARDOUS PRODUCTS REGULATIONS. THIS SAFETY DATA SHEET CONTAINS ALL INFORMATION REQUIRED BY THOSE REGULATIONS.

All components of this product appear on the domestic substance list.

NSF Certification: Hydrochloric Acid 31.45% NSF® - 60 is certified under NSF / ANSI Standard 60 for pH adjustment and as a descalter at a maximum dosage of 45 mg/L for the concentration of 31.45%. NSF product use restrictions based on requirements obtained from the NSF website; consult NSF website for current requirements.

Hydrochloric Acid (>1%) is listed in the National Pollutant Release Inventory (NPRI). Reporting threshold: 10 tonnes manufactured, processed or otherwise used.

Hydrchloric Acid is listed in the Environmental Emergency Regulations, Schedule 1. Concentration: 30% w/w Minimum Quantity: 6.8 tonnes Hazard Category: Inhalation hazard

Section 16 Other Information

Date of latest revision: August 22, 2023

Customer Service: 800.387.7503 www.cleartech.ca Emergency: 306.664.2522 Revision Date: August 22, 2023

Page 8 of 9

Note: The responsibility to provide a safe workplace remains with the buyer / user. The buyer / user should consider the health hazards and safety information contained herein as a guide and should take those precautions required in an individual operation to instruct employees and develop work practice procedures for a safe work environment. The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by the use of this material. It is the responsibility of the buyer / user to comply with all applicable laws and regulations regarding handling, using, reselling and shipping this product.

Attention: Receiver of the chemical goods / SDS coordinator

As part of our commitment to the RDC Responsible Distribution® initiative, ClearTech Industries Inc. and its associated companies require, as a condition of sale, that you forward the attached Safety Data Sheet(s) to all affected employees, customers, and end-users. ClearTech will send any available supplementary handling, health, and safety information to you at your request.

If you have any questions or concerns please call our customer service center.

References:

- 1) NIOSH Pocket Guide to Chemical Hazards; U.S. Department of Health and Human Services, https://www.cdc.gov/niosh/npg/default.html
- 2) WorkSafe BC E-Limit; Workers' Compensation Foard of British Columbia, https://elimit.online.worksafebc.com/
- 3) ECHA Registered Substance Dossier; European Chemicals Agency, https://echa.europa.eu/information-onchemicals/registered-substances
- 4) Transportation of Dangerous Goods Regulations; Transport Canada, https://laws-lois.justice.gc.ca/eng/regulations/SOR-2001-286/index.html
- 5) Globally Harmonized System of Classification and Labeling of Chemicals (GHS) Seventh revised edition
- 6) International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk (IBC Code) 2007 Edition
- 7) The ACS Style Guide

Customer Service: 800.387.7503 www.cleartech.ca Emergency: 306.664.2522 Page 9 of 9 Revision Date: August 22, 2023